

British Manufacturing since 1957



The Professionals Choice

## WMSP15 SureFlow Plus Wall Mount Water Boiler - Staniless



## **FULL SPECIFICATION**



## WMSP15 Wall Mounted SureFlow Premium Auto Fill Water Boiler

– Stainless

| Туре  | Premium Wall Mount – Wall mount Water Boiler              |
|---|---|
| Country of Design & Manufacture                             | UK  |
| CAPACITY, WEIGHTS & DIMENSIONS:                             |   |
| Capacity (Litres)   | 15  |
| Unit dimensions (W x D x H) mm                              | 370 x 250 x 530   |
| Packed dimensions (W x D x H) mm                            | 610 x 440 x 720   |
| Tap protrusion mm   | 90mm  |
| Product weight - empty (kg)                                 | 12.1  |
| Product weight – full (kg)                                  | 27.2  |
| Packed weight (kg)  | TBA   |
| CONSTRUCTION:   |   |
| Outer fabrication (body) construction                       | 304 grade stainless steel                                 |
| Tank construction   | 304 & 316 grade Stainless Steel                           |
| Tank wall thickness   | 0.9mm   |
| ELECTRICAL:   | 0.01111   |
| Power rating (kW)   | 3   |
| Voltage supply  | 220-230 V (50-60Hz)                                       |
| Electrical supply   | Single-phase, N & E (min break rating of 13amp required)  |
| Electrical Supply   | Wire into double-pole fused spare (minimum cable size:    |
|   | 1.5mm <sup>2</sup> ). Use of an ELCB is recommended       |
| DUUMPING  | 1.5mm²). Use of all ELCD is recommended                   |
| PLUMBING:   | 2/4" DCD or 15mm nuch fit                                 |
| Water inlet connection:                                     | 3/4" BSP or 15mm push-fit                                 |
| Mains water pressure range<br>Overflow/waste connection:    | 2 – 7 bar (28psi – 100psi)                                |
| Overnow/waste connection:                                   | 15mm push-fit (extend if required: pipework to have a     |
|   | continuous fall (no longer than 500mm), no more than 3    |
| DEDEODMANICE  | right-angle bends.  |
| PERFORMANCE:  |   |
| Water temperature delivered                                 | 96°C (default) – can be adjusted if required              |
| Heat up time to working temperature                         | 31 mins (full tank capacity)                              |
| Output per hour (@ default temperature setting)             | 28 Litres (higher output/hour if set @ lower temperature) |
| Rapid draw-off  | 15 Litres   |
| Recovery per minute   | 0.5 Litres  |
| Stand-by power loss (idle mode)                             | 0.12 kW/h   |
| FILTRATION:   |   |
| Multi-Filter (taste & odour, sediment & reduces lime-scale) | No (available as an optional extra if required)           |
| OTHER FEATURES:   |   |
| 7 day programmable timer                                    | Yes   |
| Energy-saving ECO mode                                      | Yes   |
| Tank-baffle plates – unique design aids heat recovery &     | Yes   |
| reduces steam emissions to atmosphere                       |   |
| Early warning lime-scale diagnostics (via LCD display)      | Yes – Advanced  |
| Dual safety protection                                      | Yes - Over-boil & boil-dry protection                     |
| STANDARDS & APPROVALS:                                      |   |
| WRAS approved   | Yes   |
| EMC Tested and Certified (EN 55014 & EN 61000)              | Yes   |
| Electrical Safety Tested and Certified to BS standard       | Yes   |
| EN 60335-1 & 2  |   |
| WARRANTY & AFTER-SALES:                                     |   |
| Guarantee   | 2 Year parts & labour                                     |
| Spare parts, filters & accessories                          | Same day despatch (if ordered before 3pm)                 |
| oparo parto, intero a accoccion                             |   |

Instanta Limited T: 01704 501114 F: 01704 501115 E: <u>sales@instanta.com</u>



Certificate Numbers: FM36413 & EMS75807