

British Manufacturing since 1957



The Professionals Choice

CTSP15PB

SureFlow Touch Push Button Counter Top Boiler



FULL SPECIFICATION



SureFlow Plus Touch Automatic Fill Water Boiler with Push Button Dispense & Programmable Locking System

Туре	Push-button Countertop - Premium Range
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	OK .
Capacity (Litres)	15
Unit dimensions (W x D x H) mm	260 x 465 x 608 (depth includes drip-tray)
	345 x 590 x 730
Packed dimensions (W x D x H) mm	145mm
Tap clearance mm	
Product weight - empty (kg)	14.2
Product weight – full (kg)	28.5
Packed weight (kg)	18.3
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Drip-tray	304 grade Stainless Steel – (Mirror polish)
ELECTRICAL:	
Power rating (kW)	3
Voltage supply	230 V (50-60Hz)
Electrical supply	Single-phase, N & E (13A)
Electrical Installation	UK standard 3-pin
Fitted cable length (m)	1.6m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Choice of front (via drip-tray) or rear (1/2"BSP – 15mm)
PERFORMANCE:	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	32 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid draw-off	12 Litres
Recovery per minute	0.5 Litre
Stand-by power loss (idle mode)	0.09 kW/h
FILTRATION:	
Multi-Filter (taste & odour, sediment & reduces lime-scale)	No (available as an optional extra if required)
OTHER FEATURES:	(a. a. a
Unique advanced locking system [3 settings],	Yes (key-fob activated)
(for high security or where health & safety is a concern)	, so (noy not destructed)
Energy saving ECO mode	Yes
Tank-baffle plates – unique design aids heat recovery &	Yes
reduces steam emissions to atmosphere	
Early warning lime-scale diagnostics (via LCD)	Yes
Dual safety protection	Yes - Over-boil & boil-dry protection
STANDARDS & APPROVALS:	2.50. 20.0 3. 20.0 4.7 p. 5.5000001
WRAS approved	Pending
EMC Tested and Certified (EN 55014 & EN 61000)	Yes (self-certified)
Electrical Safety Tested and Certified to BS standard	Yes (self-certified) - BS EN 60335-1 & 2
WARRANTY & AFTER-SALES:	100 (Soli-Collinea) - DO LIN 00000-1 (x Z
Guarantee	2 Year parts & labour
Spare parts, filters & accessories	Same day despatch (if ordered before 3pm)
opare parts, litters & accessories	Same day despatch (ii ordered before Spin)

Instanta Limited
T: 01704 501114
F: 01704 501115
E: sales@instanta.com



