



British Manufacturing
since 1957



The Professionals Choice

CTSBC2810

SmartFlow Combined Boiler & Chiller



FULL SPECIFICATION



SureFlow Automatic Fill Combined Water Boiler & Chiller

Type	Countertop, combined water boiler & chiller
Country of Design & Manufacture	UK
CAPACITY, WEIGHTS & DIMENSIONS:	
Unit dimensions (W x D x H) mm	270 x 503 x 579 (depth includes driptray)
Packed dimensions (W x D x H) mm	340 x 635 x 870
Tap clearance mm	148mm
Product weight - empty (kg)	23.5
Product weight – full (kg)	30.5
Packed weight (kg)	29.8
CONSTRUCTION:	
Outer fabrication (body) construction	304 grade Stainless Steel (Superbrush polish)
Tank construction	304 & 316 grade Stainless Steel
Tank wall thickness	0.9mm
Fridge Deck	Dry chiller [200W]
Refrigerant (chiller deck)	R290
ELECTRICAL:	
Power rating (kW)	3
Voltage supply	230 V (50/60Hz)
Electrical supply	Singlephase, N & E (13A)
Plug type	UK standard 3pin
Fitted cable length (m)	1.6m
PLUMBING:	
Water inlet connection:	3/4" BSP
Food quality, flexible mains water hose	1.6 metre long, (3/4"BSP)
Mains water pressure range	2 – 7 bar (28psi – 100psi)
Overflow/waste connection:	Choice of front (via driptray) or rear (1/2"BSP - 15mm)
PERFORMANCE (HOT):	
Water temperature delivered	96°C (default) – can be adjusted if required
Heat up time to working temperature	12 mins (full tank capacity)
Output per hour (@ default temperature setting)	28 Litres (higher output/hour if set @ lower temperature)
Rapid drawoff	3 Litres
Recovery per minute	0.5 Litres
Standby power loss (idle mode)	0.09 kW/h
PERFORMANCE (CHILLED):	
Water temperature delivered	Between 3°C and 11°C (*subject to ambient temperatures)
Output per hour	Over 60 cups per hour of chilled water @ <11°C
FILTRATION:	
MultiFilter (taste & odour, sediment & reduces limescale)	Yes (not integral)
Filter Benefits	Removes sediment & chlorine for fresh, clean tasting water
Mechanical sediment filtration	5 micron
Max filter capacity	5600 Litres

OTHER FEATURES:

Instanta Limited

T: 01704 501114

F: 01704 501115

E: sales@instanta.com



Certificate Numbers: FM01234 & EM01234